

ALL IN ONE HEAT PUMP

Features

- R290 low GWP(GWP=3).
- CMEV: Central mechanical extract ventilation.
- WIFI smart control.
- Microchannel heat exchanger.



Stable silent operation



Technical Data



Model	Primsal 200LTR	Primsal 270LTR
Heating capacity at Air 20°C/15°C, water temperature from 15° to 60°		
Heating Capacity (kW)	2.78	2.78
COP	4.15	4.15
Max Input Power (W)	3000	3000
Max Input Currently (A)	14	14
Power Supply	220-240V/50Hz	220-240V/50Hz
Heat Pump	Rated Power (W)	1200
	Rated Current (A)	5.3
Electric Heater	Rated Power (W)	1800
	Rated Current (A)	7.5
Refrigerant	R290	R290
Compressor	GMCC	GMCC
Net Dimensions (mm)	620 x 1520	620 x 1840
Package Dimensions (mm)	700 x 700 x 1665	700 x 700 x 1885
Net Weight (KG)	104	118
Gross Weight (KG)	120	136
Noise (dB)	43	43
Water Tank Volume (L)	204	278
Working Temperature Range (°C)	-7 - 43	-7 - 43
Testing condition: *Heating capacity at Air temp. 20°C / 15°		
Hot Water Production Rate (L/h)	60	60
Standard 24h Heat Loss (kWh/24h)	2.452	2.93

Option color

- Black
 White
 Grey

Primsal®

