

LED SHOPLIGHTS

Series 2

SPECIFICATIONS

| | |
|----------------|-----------------------------|
| VOLTAGE | AC 220-240V |
| POWER FACTOR | ≥ 0.90 |
| CRI | > 80 |
| RATED LIFETIME | 50,000hrs |
| BODY COLOUR | White Aluminium Coated |
| MATERIAL | Plastic |
| IP RATING | IP40 |
| IC RATING | IC-4 Abutted and Covered |
| BEAM ANGLE | 100° |
| DIMMABLE | Yes |

* This product does not consume standby power



VIVID MODELS

| MODEL | POWER | LUMEN | DIMENSIONS | CUTOUT | CCT SWITCHABLE |
|--------------|-------|-------|------------|--------|----------------------|
| PDL5W70CCT | 5W | 500 | ø92x62mm | ø70mm | 3000K 4000K 5000K |
| PDL8W90CCT | 8W | 800 | ø110x70mm | ø90mm | 3000K 4000K 5000K |
| PDL8W150CCT | 8W | 1000 | ø190x85mm | ø150mm | 3000K 4000K 5000K |
| PDL18W150CCT | 18W | 1800 | ø190x85mm | ø150mm | 3000K 4000K 5000K |
| PDL8W200CCT | 8W | 1000 | ø230x95mm | ø200mm | 3000K 4000K 5000K |
| PDL18W200CCT | 18W | 1800 | ø230x85mm | ø200mm | 3000K 4000K 5000K |

GET IN TOUCH

 info@primsal.com

 primsal.com