

# ILUMINOUS

by **Primsal**®

## LED Sensor Batten

### Series 3

#### SPECIFICATIONS

VOLTAGE 220-240AC

POWER FACTOR >0.90

CRI >80

IP RATING IP20

BEAM ANGLE 110°

Occupancy and Daylight built in Sensor:

MOUNTING HEIGHT 3.5m

DETECTION RANGE 6m Diameter

DAYLIGHT THRESHOLD 450 Lux

MOTION HOLD TIME 20mins

POWER SAVING MODE 30% dim

ACCESSORIES Remote Control (Sensor ON / Sensor OFF / 30% dim)



\* This product does not have a standby mode, therefore does not consume standby power

#### ILUMINOUS

MODEL	POWER	LUMEN	DIMENSIONS	CCT
PBT16W9X124KCS PBT16W9X125KCS	16w	2640	1200x85x80mm	4000K 5000K
PBT25W9X124KCS PBT25W9X125KCS	25w	4125	1200x85x80mm	4000K 5000K
PBT40W9X124KCS PBT40W9X125KCS	40w	6600	1200x85x80mm	4000K 5000K
PBT25W9X154KCS PBT25W9X155KCS	25w	4125	1500x85x80mm	4000K 5000K
PBT40W9X154KCS PBT40W9X155KCS	40w	6600	1500x85x80mm	4000K 5000K

GET IN TOUCH

 [info@primsal.com](mailto:info@primsal.com)

 [primsal.com](http://primsal.com)

