

LED HIGH BAY

Series 3

SPECIFICATIONS

VOLTAGE	220-240V 50/60Hz	MOTION AND DAY LIGHT MICROWAVE SENSOR
POWER FACTOR	≥ 0.90	FREQUENCY 5.8GHz ±75MHz
COLOUR TEMPERATURE	5000K	INPUT VOLTAGE 12~24V
RATED LIFETIME	>50,000hrs	MOUNT HEIGHT Up to 13m
BODY COLOUR	Black	SENSIVITY 100%
IP RATING	IP65	DETECTION RANGE Up to 8m diameter
BEAM ANGLE	90°	DETECTION AREA 360°
MATERIAL	Die-Cast Aluminium, PC Lens	DAYLIGHT THRESHOLD 500lux
CRI	70	MOTION HOLD TIME 15mins
CABLE LENGTH	1.5m + Plug	STANDBY DIMMING 20%
OPTIONAL EXTRAS	Reflector, Mounting bracket	REMOTE CONTROL sensor OFF sensor ON dim 20%



TITAN MODELS Series 3

MODEL	POWER	LUMEN	DIMENSIONS	CCT
PHB5050S	50W	11000	265x110x155mm	5000K
PHB6050S	60W	13500	265x110x155mm	5000K
PHB8050S	80W	18000	265x110x155mm	5000K
PHB9550S	95W	20000	265x110x155mm	5000K
PHB15050S	150W	31000	265x110x155mm	5000K
PHB20050S	200W	41000	310x110x155mm	5000K

GET IN TOUCH

 info@primsal.com

 primsal.com