

Weatherproof Sensor Batten

SPECIFICATIONS

VOLTAGE	220-240AC
POWER FACTOR	>0.90
CRI	>80
LIFETIME	>50,000
IP RATING	IP65
IMPACT RATING	IK08
BEAM ANGLE	110°

Occupancy and Daylight built in Sensor:

MOUNTING HEIGHT	3.5m
DETECTION RANGE	8m Diameter
DAYLIGHT THRESHOLD	60 Lux 160 Lux
MOTION HOLD TIME	20mins
POWER SAVING MODE	30% dim
REMOTE CONTROL	Sensor ON / Sensor OFF / 30% dim



Features

- PA16 Terminal block
- 5x20mm entry points
- 20mm cable gland
- Safety Lanyards

* This product does not have a standby mode, therefore does not consume standby power

ILUMINOUS MODELS

MODEL	POWER	LUMEN	DIMENSIONS	CCT
PWB10W66X84KS PWB10W66X85KS	10w	1600	660x80x72mm	4000K 5000K
PWB16W120X84KS PWB16W120X85KS	16w	2600	1200x80x72mm	4000K 5000K
PWB20W150X84KS PWB20W150X85KS	20w	3250	1500x80x72mm	4000K 5000K
PWB40W150X134KS PWB40W150X135KS	40w	6000	1500x130x88mm	4000K 5000K

GET IN TOUCH

 info@primsal.com

 primsal.com